

GALLOWAY

GLAZED PORCELAIN | FLOOR & WALL TILES

WOOD EFFECT TILES | ABSOLUTE



JOHNSON • TILES 

MADE IN THE UK SINCE 1901

GALLOWAY

Galloway, inspired by parquet flooring, features three colours ranging from light Birch to deep Walnut. Engaging with shape, Galloway offers four framed designs of Maise, Basketweave, Cross and Chevron. Maise and Basketweave play with overlay to create dynamic configurations, whilst Cross and Chevron explore diagonals. Slim format plank options and co-ordinating skirtings are also available.

Front Cover Image: Walnut Natural 1190x200mm - GLW03N & Walnut Basketweave Natural 600x600mm - GLW03B





Roomset Photography





Colours & Product Codes

V3: Moderate to High Shade Variation



BIRCH

N GLW01N + **G** GLW01G
PEI: IV LRV: 42



OAK

N GLW02N + **G** GLW02G
PEI: IV LRV: 40



WALNUT

N GLW03N + **G** GLW03G
PEI: III LRV: 15



BIRCH MAIZE
N GLW01M PEI: IV LRV: 42



OAK MAIZE
N GLW02M PEI: IV LRV: 40



WALNUT MAIZE
N GLW03M PEI: III LRV: 15



BIRCH BASKETWEAVE
N GLW01B PEI: IV LRV: 42



OAK BASKETWEAVE
N GLW02B PEI: IV LRV: 40



WALNUT BASKETWEAVE
N GLW03B PEI: III LRV: 15



BIRCH CROSS
N GLW01C PEI: IV LRV: 42



OAK CROSS
N GLW02C PEI: IV LRV: 40



WALNUT CROSS
N GLW03C PEI: III LRV: 15



BIRCH CHEVRON
N GLW01V PEI: IV LRV: 42




OAK CHEVRON
N GLW02V PEI: IV LRV: 40



WALNUT CHEVRON
N GLW03V PEI: III LRV: 15




Sizes, Finishes & Availability



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	1190x200mm	(N) Natural	All Colours Shown	10.5mm	3 Tiles	0.72 m ²	17.20 kg
		(G) Grip	All Colours Shown	10.5mm	3 Tiles	0.72 m ²	17.20 kg
2	600x600mm Maise	(N) Natural	All Colours Shown	9.2mm	3 Tiles	1.08 m ²	23.03 kg
3	600x600mm Basketweave	(N) Natural	All Colours Shown	9.2mm	3 Tiles	1.08 m ²	23.03 kg
4	600x600mm Cross	(N) Natural	All Colours Shown	9.2mm	3 Tiles	1.08 m ²	23.03 kg
5	600x600mm Chevron	(N) Natural	All Colours Shown	9.2mm	3 Tiles	1.08 m ²	23.03 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.



Walnut Grip 1190x200mm - GLW03G
Walnut Chevron Natural 600x600mm - GLW03V





Additional Fittings

V3: Moderate to High Shade Variation



BIRCH

N GLW1NS **LRV. 42**



OAK

N GLW2NS **LRV. 40**



WALNUT

N GLW3NS **LRV. 15**



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	600x95mm Round Top Skirting	N Natural	All Colours Shown	9.2mm	20 Tiles	12.00 lm	24.00 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.



Oak Cross Natural 600x600mm - GLW02C





Technical Data

Specification

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Galloway	All Sizes Shown	Internal & External	Internal Only	-	V3	Glazed Porcelain [Bla]
Galloway	1190x200x10.5mm	Internal & External	Internal & External	Yes	V3	Glazed Porcelain [Bla]

Floor Values

Finish	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
Natural	Walnut	Dry 36+ Wet 25 - 35	-	-	-	III	Light Commercial
Natural	All Other Colours	Dry 36+ Wet 25 - 35	-	-	-	IV	Commercial
Grip	Walnut	Dry 36+ Wet 36+	Wet 36+	R II	-	III	Light Commercial
Grip	All Other Colours	Dry 36+ Wet 36+	Wet 36+	R II	-	IV	Commercial

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. PTV: Pendulum Test Value.

Physical Properties

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm ²	$\geq 45\text{N} / \text{mm}^2$
Thickness EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	$\pm 3\%$	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	$\pm 0.3\%$	Frost Resistance EN ISO 10545 - 12	Resistant	Resistant
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Min. Class B
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Min. Class 3
Water Absorption EN ISO 10545 - 3	$\leq 0.5\%$	$\leq 0.1\%$	Fire Rating	-	Class A I _{FL} Non Combustible
Weight / M²	22.60 kg 10.5mm thick	21.33 kg 9.2mm thick			

Note: All products are classed as Bla - Glazed Porcelain. All products conform to BS EN 14411.

Sustainability Information

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD	SKA Rating
Galloway	Glazed Porcelain [Bla]	Up to 10%	Up to 100% (Boxes)	Up to 100%	Yes	-

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Galloway pages on our website.

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.



For more information about Galloway or
any of our other product ranges simply visit
www.johnson-tiles.com |      

Where To Find Us

Johnson Tiles

Harewood Street,
Tunstall,
Stoke on Trent,
Staffordshire,
ST6 5JZ

Tel: +44 (0)1782 575 575
Fax: +44 (0)1782 577 377
Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0)1782 524 043
Fax: +44 (0)1782 577 379
Email: samples@johnson-tiles.com

Technical Helpline

Tel: +44 (0)1782 524 111
Fax: +44 (0)1782 577 379
Email: techadvice@johnson-tiles.com

Launched: February 2021

JOHNSON • TILES 
MADE IN THE UK SINCE 1901