

GLADEMOOR

GLAZED PORCELAIN & CERAMIC | FLOOR & WALL TILES

STONE SELECT



JOHNSON • TILES 

MADE IN THE UK SINCE 1901

GLADEMOOR



6 SIZES



5 COLOURS



5 FINISHES

Replicating natural materials, Glademoor takes direction from the interiors trend for earth tones with five colours of Stone, Sand, Flint, Coal, and Bone. Glademoor also features two mixed décor options which combine hues from across the colour palette to create a stylish focal point for added detail and surface interest, whilst the weave structured design delivers a stunning statement to combine seamlessly with the field tiles. The Grip and Grip+ finishes both provide a PTV slip resistance rating of 36+ to add to the versatility of this range.





Flint Natural 600x300x9.2mm - GLA04N
Flint Grip 600x300x9.2mm - GLA04G



Flint Matt 890x300x10.5mm - GLA04M
 Flint Weave Structure Matt 890x300x10.5mm - GLA04W
 Flint Natural 600x600x10.5mm - GLA04N




Stone Grip+ 600x600x20mm - GLA02E (2cm)



Bone Matt 890x300x10.5mm - GLA01M
 Bone Weave Structure Matt 890x300x10.5mm - GLA01W
 Bone Natural 600x600x9.2mm - GLA01N



Size Formats Sizing & Packing Information



#	Size	Thickness	Finish	Structure	Colour Availability	Pcs / Box	M2 / Box	Kg / Box
1	600x600mm	9.2mm	(N) Natural	-	All Colours	3 Tiles	1.08m ²	23.03kg
			(L) Lapato	-	All Colours	3 Tiles	1.08m ²	23.03kg
		20mm	(G) Grip	-	All Colours	3 Tiles	1.08m ²	23.03kg
			(E) Grip+	-	Bone, Stone & Flint Only	2 Tiles	0.72m ²	32.02kg
2	600x300mm	9.2mm	(N) Natural	-	All Colours	5 Tiles	0.90m ²	19.26kg
			-	-	Mix Décors Only	6 Tiles	1.08m ²	23.03kg
			(L) Lapato	-	All Colours	5 Tiles	0.90m ²	22.36kg
3	450x450mm	9.2mm	(G) Grip	-	All Colours	5 Tiles	0.90m ²	19.26kg
			(N) Natural	-	All Colours	5 Tiles	1.02m ²	21.50kg
			(L) Lapato	-	All Colours	5 Tiles	1.02m ²	21.50kg
4	485x300mm Mixed Strip Mosaic	9.2mm	(G) Grip	-	All Colours	5 Tiles	1.02m ²	21.50kg
			(N) Natural	-	All Colours	6 Sheets	0.88m ²	17.34kg
5	300x300mm (50x50mm) Square Mosaic	9.2mm	(L) Lapato	-	All Colours	6 Sheets	0.88m ²	17.34kg
			(N) Natural	-	All Colours	10 Sheets	0.90m ²	16.80kg
6	890x300mm	10.5mm	(M) Matt	-	Bone, Stone, Flint & Coal Only	5 Tiles	1.34m ²	22.04kg
			(M) Matt	Weave		5 Tiles	1.34m ²	22.04kg
#	Fitting	Thickness	Finish	Structure	Colour Availability	Pcs / Box	LM / Box	Kg / Box
7	600x95mm Round Top Skirting	9.2mm	(N) Natural	-	All Colours	18 Tiles	10.80lm	17.80kg
			(L) Lapato	-	All Colours	18 Tiles	10.80lm	17.80kg
8	450x95mm Round Top Skirting	9.2mm	(N) Natural	-	All Colours	23 Tiles	10.35lm	20.00kg
			(L) Lapato	-	All Colours	23 Tiles	10.35lm	20.00kg
9	300x95mm Round Top Skirting	9.2mm	(N) Natural	-	All Colours	30 Tiles	9.00lm	17.80kg
			(L) Lapato	-	All Colours	30 Tiles	9.00lm	17.80kg

Note: All sizes indicated are metric modular. All sizes shown are nominal. (R) Rectified Edge - Matt, Lapato & Grip+ Finishes Only.
For the most up-to-date product availability information for this range, please visit our website - www.johnson-tiles.com



Colours & Product Codes

V3: Moderate to High Shade Variation



BONE (LRV: 86) (PEI: V)

Product Codes (Bla): (N) GLA01N + (L) GLA01L + (G) GLA01G + (E) GLA01E

Mosaic Codes: (N) GLA1NM + (L) GLA1LM | Fitting Codes: (N) GLA1NS + (L) GLA1LS



STONE (LRV: 80) (PEI: V)

Product Codes (Bla): (N) GLA02N + (L) GLA02L + (G) GLA02G + (E) GLA02E

Mosaic Codes: (N) GLA2NM + (L) GLA2LM | Fitting Codes: (N) GLA2NS + (L) GLA2LS



SAND (LRV: 66) (PEI: V)

Product Codes (Bla): (N) GLA03N + (L) GLA03L + (G) GLA03G

Mosaic Codes: (N) GLA3NM + (L) GLA3LM | Fitting Codes: (N) GLA3NS + (L) GLA3LS



Colours & Product Codes

V3: Moderate to High Shade Variation



FLINT LRV: 55 PEI: IV

Product Codes (Bla): N GLA04N + L GLA04L + G GLA04G + E GLA04E

Mosaic Codes: N GLA4NM + L GLA4LM | Fitting Codes: N GLA4NS + L GLA4LS



COAL LRV: 22 PEI: IV

Product Codes (Bla): N GLA05N + L GLA05L + G GLA05G

Mosaic Codes: N GLA5NM + L GLA5LM | Fitting Codes: N GLA5NS + L GLA5LS



BONE, STONE & SAND MIX DÉCOR

Product Codes (Bla): N GLA01D



FLINT & COAL MIX DÉCOR

Product Codes (Bla): N GLA02D



Colours & Product Codes

V3: Moderate to High Shade Variation



BONE (LRV: 86)

Product Codes (BIII) Wall Tiles Only: (M) GLA01M



BONE WEAVE STRUCTURE (LRV: 86)

Product Codes (BIII) Wall Tiles Only: (M) GLA01W



STONE (LRV: 80)

Product Codes (BIII) Wall Tiles Only: (M) GLA02M




STONE WEAVE STRUCTURE (LRV: 80)

Product Codes (BIII) Wall Tiles Only: (M) GLA02W



FLINT (LRV: 55)

Product Codes (BIII) Wall Tiles Only: (M) GLA04M




FLINT WEAVE STRUCTURE (LRV: 55)

Product Codes (BIII) Wall Tiles Only: (M) GLA04W



COAL (LRV: 22)

Product Codes (BIII) Wall Tiles Only: (M) GLA05M



COAL WEAVE STRUCTURE (LRV: 22)

Product Codes (BIII) Wall Tiles Only: (M) GLA05W



Technical, Sustainability & Important Information

Specification

Range	Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Glademoor	N Natural	Internal & External	Internal Only	-	V3	Glazed Porcelain (Bla)
	L Lapato	Internal & External	Internal Only	-	V3	Glazed Porcelain (Bla)
	G Grip	Internal & External	Internal & External	Yes	V3	Glazed Porcelain (Bla)
	E Grip+	-	Internal & External	Yes	V3	Glazed Porcelain (Bla)
	M Matt	Internal Only	-	-	V3	Glazed Ceramic (BIII)

Floor Values

Finish	Structure	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
N Natural	-	Flint & Coal	Dry 36+ Wet 0 - 24	-	-	-	IV	Commercial
	-	All Other Colours	Dry 36+ Wet 0 - 24	-	-	-	V	Heavy Commercial
L Lapato	-	Flint & Coal	Dry 36+ Wet 0 - 24	-	-	-	IV	Commercial
	-	All Other Colours	Dry 36+ Wet 0 - 24	-	-	-	V	Heavy Commercial
G Grip	-	Flint & Coal	Dry 36+ Wet 36+	Wet 36+	R 11	C	IV	Commercial
	-	All Other Colours	Dry 36+ Wet 36+	Wet 36+	R 11	C	V	Heavy Commercial
E Grip+	-	Flint	Dry 36+ Wet 36+	Wet 36+	R 11	B	IV	Commercial
	-	All Other Colours	Dry 36+ Wet 36+	Wet 36+	R 11	B	V	Heavy Commercial

Physical Properties - Glazed Porcelain (Bla)

Test & Standard	Requirement	Test Result	Test & Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Modulus of Rupture EN ISO 10545 - 4	Min. 35N / mm ²	$\geq 45\text{N} / \text{mm}^2$
Thickness EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	$\pm 3\%$	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	$\pm 0.3\%$	Frost Resistance EN ISO 10545 - 12	Resistant	Resistant
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Min. Class B
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	$\pm 0.3\%$	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Min. Class 3
Water Absorption EN ISO 10545 - 3	$\leq 0.5\%$	$\leq 0.1\%$	Fire Rating	-	Class A I _{FL} Non Combustible
Weight / M ²	23.09kg 10.5mm thick	21.40kg 9.2mm thick			

Physical Properties - Glazed Ceramic (BIII)

Test & Standard	Requirement	Test Result	Test & Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Modulus of Rupture EN ISO 10545 - 4	Min. 15N / mm ²	Pass
Thickness EN ISO 10545 - 2	$\pm 10\% \leq \pm 0.5\text{mm}$	Pass	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	$\pm 0.3\% \leq \pm 1.5\text{mm}$	Pass	Frost Resistance EN ISO 10545 - 12		Not Suitable
Rectangularity EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Min. Class B
Surface Flatness EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Min. Class 3
Water Absorption EN ISO 10545 - 3	10% to 20%	16% to 19%	Fire Rating	-	Class A I Non Combustible
Weight / M ²	18.01 kg 10.5mm thick				

Technical, Sustainability & Important Information

Sustainability Information

Range	Material	EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Glademoor	Glazed Porcelain (BIa)	Yes	Up to 10%	Up to 100% (Boxes)	Up to 100%
	Glazed Cermaic (BIII)	Yes	Up to 10%	Up to 100% (Boxes)	Up to 100%

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. Please contact our technical helpline, or visit our website for specification and installation advice. All glazed porcelain (BIa) and glazed ceramic (BIII) products listed conform to BS EN 14411. CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 55. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute. For a full overview of our environmental credentials please visit www.johnson-tiles.com/about/sustainability. EPD: Environmental Product Declaration.

Important Information

During the manufacturing process of ceramic and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed. For a comprehensive colour, size and finish overview along with full technical and sustainability information for all of the product shown in this product presenter, please visit our website - www.johnson-tiles.com.

- All sizes shown are metric modular.
- For specific suitability details please contact our technical department.
- Johnson Tiles cannot accept responsibility for tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specification and availability information without prior notice.
- Nothing in these statements does/will affect the statutory rights of the consumer.



All product technical values quoted in this product presenter are supported by laboratory testing from our own and independent ceramic test houses. Johnson Tiles are British Standard registered and all products conform to the standards set in BS EN 14411.

For the reassurance of single-source supply, Johnson Tiles offers a free of charge NBS M40 specification writing service featuring the Norcros Adhesives range of tile fixing products. To find out more or for any questions or queries relating to any tile related technical information featured in this product presenter, please contact our technical advice helpline on +44 (0)1782 524 111 or email ddunlop@johnson-tiles.com

The colours shown in this sample tile wallet and attached booklet are as accurate as printing processes will allow. Please refer to actual product samples before specifying. Every effort has been made to ensure the accuracy of the information given.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2022 Johnson Tiles. All rights reserved.



Coal Natural 600x300x9.2mm - GLA05N
 Flint & Coal Mix Décor Natural 600x300x9.2mm - GLA02D
 Flint Natural 600x600x9.2mm - GLA04N

For more information about Glademoor or any of our other product ranges simply visit

www.johnson-tiles.com | [f](#) [t](#) [i](#) [p](#) [in](#) [v](#)

Where To Find & Contact Us

Johnson Tiles Head Office

Harewood Street, Tunstall,
Stoke on Trent, Staffordshire,
ST6 5JZ, United Kingdom

Tel: +44 (0)1782 575 575
Email: info@johnson-tiles.com
www.johnson-tiles.com

Material Lab Studio

10 Great Titchfield Street,
London, W1W 8BB,
United Kingdom

Tel: +44 (0)20 7436 8629
Email: info@material-lab.co.uk
www.material-lab.co.uk

Johnson Tiles Factory Outlet

Tel: +44 (0)1782 524 040
Email: foutlet@johnson-tiles.com
www.outlet.johnson-tiles.com

Customer Services

Tel: +44 (0)1782 524 000
Email: sales@johnson-tiles.com

Order A Sample

Tel: +44 (0)1782 524 043
Email: samples@johnson-tiles.com

Technical Advice

Tel: +44 (0)1782 524 111
Email: ddunlop@johnson-tiles.com

Launched: March 2022 • Updated: March 2023

JOHNSON • TILES 
MADE IN THE UK SINCE 1901

Johnson Tiles is a division of Norcross Group (Holdings) Limited,
Ladyfield House, Station Road, Wilmslow, Cheshire, SK9 1BU,
United Kingdom. Registered in England number 566694.