

# PARADE

UN-GLAZED PORCELAIN | FLOOR & WALL TILES

PLAIN COLOUR TILES



# PARADE

A contemporary porcelain floor tile range, Parade is perfect for creating a classic look. With a Polished finish, Parade offers a luxurious sheen in an understated White in either 600x300mm or 600x600mm sizes.

Front Cover Image: White Polished 600x300mm - PAR01P




White Polished 600x600mm - PAR01P





## Colours & Product Codes

V1: Low Shade Variation






**WHITE**

 PAR01P  LRV: 64



## Sizes, Finishes & Availability



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	600x600mm	 Polished	White	10mm	4 Tiles	1.44 m <sup>2</sup>	28.00 kg
2	600x300mm	 Polished	White	9mm	6 Tiles	1.08 m <sup>2</sup>	21.00 kg

**Note:** All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.





## Technical Data

### Specification

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Parade	All Sizes Shown	Internal & External	Internal Only	-	VI	Un-glazed Porcelain [Bla]

### Floor Values

Finish	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
Polished	All Colours Shown	Dry 36+ Wet 0 - 24	-	-	-	-	Commercial

**Note:** Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. PTV: Pendulum Test Value.

### Physical Properties

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
<b>Length / Width</b> EN ISO 10545 - 2	$\pm 0.6\% \leq \pm 2\text{mm}$	Pass	<b>Modulus of Rupture</b> EN ISO 10545 - 4	Min. 35N / mm <sup>2</sup>	$\geq 47\text{N} / \text{mm}^2$
<b>Thickness</b> EN ISO 10545 - 2	$\pm 5\% \leq \pm 0.5\text{mm}$	Pass	<b>Thermal Shock</b> EN ISO 10545 - 9	Pass	Pass
<b>Straightness of Side</b> EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 1.5\text{mm}$	Pass	<b>Frost Resistance</b> EN ISO 10545 - 12	Resistant	Resistant
<b>Rectangularity</b> EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	<b>Chemical Resistance</b> EN ISO 10545 - 13	Min. Class B	Pass
<b>Surface Flatness</b> EN ISO 10545 - 2	$\pm 0.5\% \leq \pm 2\text{mm}$	Pass	<b>Stain Resistance</b> EN ISO 10545 - 14	Min. Class 3	Pass
<b>Water Absorption</b> EN ISO 10545 - 3	$\leq 0.5\%$	$\leq 0.08\%$	<b>Fire Rating</b>	-	Class A I <sub>FL</sub> Non Combustible
<b>Weight / M<sup>2</sup></b>	<b>21.88 kg</b> 10mm thick	<b>19.45 kg</b> 9mm thick			

**Note:** All products are classed as Bla - Un-glazed Porcelain. All products conform to BS EN 14411.

### Sustainability Information

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD	SKA Rating
Parade	Un-glazed Porcelain [Bla]	-	-	Up to 100%	-	-

### Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

© Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.



For more information about Parade or any  
of our other product ranges simply visit  
**[www.johnson-tiles.com](http://www.johnson-tiles.com)** |      

#### **Where To Find Us**

##### **Johnson Tiles**

Harewood Street,  
Tunstall,  
Stoke on Trent,  
Staffordshire,  
ST6 5JZ

Tel: +44 (0)1782 575 575  
Fax: +44 (0)1782 577 377  
Email: [info@johnson-tiles.com](mailto:info@johnson-tiles.com)

---

##### **Samples Enquiries**

Tel: +44 (0)1782 524 043  
Fax: +44 (0)1782 577 379  
Email: [samples@johnson-tiles.com](mailto:samples@johnson-tiles.com)

---

##### **Technical Helpline**

Tel: +44 (0)1782 524 111  
Fax: +44 (0)1782 577 379  
Email: [techadvice@johnson-tiles.com](mailto:techadvice@johnson-tiles.com)

**JOHNSON • TILES**   
MADE IN THE UK SINCE 1901