

PORCELAIN & CERAMIC | FLOOR & WALL TILES

## MARBLE 2CM MOSAICS (ABSOLUTE)








# BUCKINGHAM

Inspired by the character of marble, and with highlights of striking veins adding subtle, understated detail, Buckingham provides a modern, sophisticated aesthetic. Available in sizes from 600x300mm up to 2700x120mm, Buckingham showcases a timeless colour palette from the luxurious warmth of Sand to the richness of Anthracite. This commercial collection offers finishes of Soft Bush Hammered, Grip, and Grip+ 2cm, with co-ordinating mosaics and skirtings also included.

Front Cover Image: Anthracite Soft Bush Hammered 2700x900mm Ductile – BUC4DB and Anthracite Soft Bush Hammered 1200x1200mm – BUCK4B.









**Colours & Product Codes** V2: Low to Moderate Shade Variation



SAND LRV: 45

Product Codes (All Sizes): B BUCK5B + B BUC5DB Ductile + G BUCK5G Mosaic Product Codes (All Sizes): B BUC5BM + G BUC5GM




Product Codes (All Sizes): B BUCK2B + B BUC2DB Ductile + G BUCK2G + E BUCK2E 2cm Mosaic Product Codes (All Sizes): B BUC2BM + G BUC2GM



#### GREY LRV: 29

Product Codes (All Sizes): B BUCK3B + B BUC3DB Ductile + G BUCK3G Mosaic Product Codes (All Sizes): B BUC3BM + G BUC3GM




# Product Codes (All Sizes): B BUCK4B + B BUC4DB Ductile + G BUCK4G

Mosaic Product Codes (All Sizes): B BUC4BM + G BUC4GM



### Size Formats

Finishes & Availability



#	Sizes	Finish Type	Colour Availability	Thickness	Pz / Box	M2 / Box	Kg / Box
I	2700x1200mm	B Only	All Colours Shown	6mm	I Tile	3.23 m²	45.50 kg
2	2700x900mm	B Ductile	All Colours Shown	6mm	I Tile	2.42 m <sup>2</sup>	29.04 kg
3	200x 200mm	B+G	All Colours Shown	9mm	I Tile	1.44 m²	30.50 kg
J	1200012001111	E 2cm	02 Only	20mm	I Tile	1.44 m²	66.02 kg
4	1200x600mm	B+G	All Colours Shown	9mm	2 Tiles	1.43 m²	30.32 kg
4	12000000000	B Ductile	All Colours Shown	6mm	3 Tiles	2.16 m <sup>2</sup>	25.80 kg
5	900x900mm	B+G	All Colours Shown	9mm	2 Tiles	1.62 m²	34.00 kg
J	900000000000000000000000000000000000000	E 2cm	02 Only	20mm	I Tile	0.81 m²	37.09 kg
6	900x450mm	B + G	All Colours Shown	9mm	3 Tiles	1.2 l m²	25.50 kg
7	600x600mm	B+G	All Colours Shown	9mm	3 Tiles	1.07 m <sup>2</sup>	23.22 kg
8	600x300mm	B+G	All Colours Shown	9mm	6 Tiles	1.07 m <sup>2</sup>	22.00 kg


#	Mosaics	Finish Type	Colour Availability	Thickness	Pz / Box	M2 / Box	Kg / Box
9	25x25mm Square Mosaic Sheet: 300x300mm	B + G	All Colours Shown	9mm	5 Sheets	0.44 m²	9.00 kg
10	50x50mm Square Mosaic Sheet: 300x300mm	B + G	All Colours Shown	9mm	5 Sheets	0.44 m²	9.00 kg
11	Mixed Strips Mosaic Sheet: 450x300mm	B + G	All Colours Shown	9mm	5 Sheets	0.44 m²	9.00 kg
12	<b>3D Strips Mosaic</b> Sheet: 900x150mm	B + G	All Colours Shown	9mm	4 Sheets	0.35 m²	7.50 kg
13	<b>Deco Mosaic</b> Sheet: 600x600mm	B + G	All Colours Shown	9mm	3 Sheets	0.89 m²	19.00 kg

Key to Finishes:  $\ensuremath{\mathbb{B}}$  Soft Bush Hammered  $\ensuremath{\mathbb{G}}$  Grip  $\ensuremath{\mathbb{E}}$  Grip+ 2cm

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value. Rectified Edge Ductile - 6mm thick tiles are classed as Ceramic [BIII] and are suitable for internal and external wall applications only.




#### Additional Fittings Finishes & Availability



Key to Finishes: B Soft Bush Hammered

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.





#### Specification

Range	Size / Finish	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
	All Sizes Shown B	Internal & External	Internal Only	-	V2	Porcelain [Bla]
Buckingham	All Sizes Shown G	Internal & External	Internal & External	Yes	V2	Porcelain [BIa]
	All Sizes Shown 🗉	Internal & External	Internal & External	Yes	V2	Porcelain [Bla]
<b>Buckingham</b> Ductile	All Sizes Shown B	Internal Only	-	-	V2	Ceramic [BIII]

#### **Floor Values**

Finish	Colour	PTV (4S)	PTV (TRL)	R Value	Wet Ramp	PEI	Traffic
B Soft Bush Hammered	All Colours Shown	Dry 36+ Wet 25 - 35	-	R 9	А	-	Commercial
G Grip	All Colours Shown	Dry 36+ Wet 36+	Wet 36+	RII	С	-	Commercial
E Grip+ 2cm	All Colours Shown	Dry 36+ Wet 36+	Wet 36+	RII	С	-	Commercial

Note: Due to the manufacturing process of all floor tiles there may be small variations in slip resistance. Given this, please refer to our website for the most up-to-date information. The slip resistance properties of a surface can only be maintained with the implementation of an effective regular cleaning and maintenance regime. The frequency of cleaning should be determined by the property manager based on the potential level of surface contaminants. The need for an additional regular cleaning and maintenance regime is further heightened when tiles are used for external floor and wet barefoot applications. CSV: Colour Shade Variation. PTV (4S): Pendulum Test Value - Slider 96. PTV (TRL): Pendulum Test Value - Slider 55. R Value (DIN 51130). Wet Ramp (DIN 51097). PEI: Porcelain Enamel Institute.

#### Physical Properties - Porcelain [Bla]

Test / Standard	Requirement	Test Result	Test / Standard Requirement Test Result
Length / Width EN ISO 10545 - 2	± 0.6% ≤ ± 2mm	Pass	Modulus of Rupture     Min. 35N / mm²     ≥ 52N / mm²       EN ISO 10545 - 4     Min. 35N / mm²     ≥ 52N / mm²
→ Thickness ► INISO 10545 - 2	± 5% ≤ ± 0.5mm	Pass	Thermal Shock Pass Pass Pass
Straightness of Side EN ISO 10545 - 2	± 0.5% ≤ ± 1.5mm	Pass	Frost Resistance EN ISO 10545 - 12 Resistant Resistant
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Chemical Resistance EN ISO 10545 - 13 Min. Class B Pass
► Surface Flatness ► INISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Stain Resistance EN ISO 10545 - 14 Min. Class 3 Class 5
Water Absorption EN ISO 10545 - 3	≤ 0.5%	≤ 0.5%	Fire Rating - Class A IFL Non Combustibl
kg Weight / M <sup>2</sup>	<b>14.09 kg</b> 6mm thick	<b>2 I.I 9 kg</b> 9mm thick	<b>45.85 kg</b> 20mm thick

#### Physical Properties - Ceramic [BIII] Ductile

Test / Standard	Requirement	Test Result	Test / Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Modulus of Rupture EN ISO 10545 - 4	Min. 15N / mm²	≥ 20N / mm²
→ Thickness ► EN ISO 10545 - 2	± 10% ≤ ± 0.5mm	Pass	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.3% ≤ ± 1.5mm	Pass	<b>Frost Resistance</b> EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A
→ Surface Flatness ►↑↑ EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	Pass	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 5
Water Absorption EN ISO 10545 - 3	10% to 20%	10% to 20%	Fire Rating	-	Class A1 Non Combustible
kg Weight / M <sup>2</sup>	<b>10.68 kg</b> 6mm thick Ductile				

Note: All Porcelain [BIa] and Ceramic [BIII] Ductile products listed in this overview conform to BS EN 14411.

#### arnothing Sustainability Information

Range		EPD	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging
Buckingham	Porcelain [BIa]	Yes	Up to 30%	Up to 100% (Boxes)	Up to 100% (Boxes)
Buckingham Ductile	Ceramic [BIII]	Yes	Up to 30%	Up to 100% (Boxes)	Up to 100% (Boxes)

Note: EPD: Environmental Product Declaration for the products shown in this overview can be found on the Buckingham pages on our website.


#### Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

 Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.





Product Notes For more information about Buckingham or any of our other product ranges simply visit www.johnson-tiles.com | f ♥ @ ? in ■

#### Where To Find Us

Johnson Tiles Harewood Street, Tunstall, Stoke on Trent, Staffordshire, ST6 5JZ

Tel: +44 (0)1782 575 575 Fax: +44 (0)1782 577 377 Email: info@johnson-tiles.com

#### Samples Enquiries

Tel: +44 (0)1782 524 043 Fax: +44 (0)1782 577 379 Email: samples@johnson-tiles.com

#### Technical Helpline

Tel: +44 (0)1782 524 111 Fax: +44 (0)1782 577 379 Email: techadvice@johnson-tiles.com

Launched: June 2018 Updated: January 2022

