
HARBOUR

GLAZED CERAMIC | WALL TILES

STONE EFFECT TILES SELECT












HARBOUR


Harbour encapsulates the aesthetic of sea-weathered rocks with distressed markings and a structured finish. Available in 3 colourways of Sea Spray, Quay Grey and Breakwater, Harbour is perfect to create a rustic ambience. Sea Spray displays fresh tones of white; Quay Grey is reminiscent of sea-washed pebbles while Breakwater showcases a darker grey shade.

Front Cover Image: Sea Spray Rock Texture Matt 400x150mm - HARBIT





Roomset Photography







03 www.johnson-tiles.com



Colours & Product Codes

V3: Moderate to High Shade Variation



SEA SPRAY ROCK STRUCTURE
M HARBIT LRV: 73



QUAY GREY ROCK STRUCTURE
M HARB2T LRV: 53



BREAKWATER ROCK STRUCTURE
M HARB3T LRV: 38



Sizes, Finishes & Availability



#	Size	Finish	Colour Availability	Thickness	Pieces/Box	Coverage/Box	Weight/Box
1	400x150mm Rock Structure	M Matt	All Colours Shown	I 0 mm	17 Tiles	1.02 m ²	17.00 kg

Note: All sizes indicated are metric modular. All dimensions are in millimetres. All sizes shown are nominal. For the most up-to-date availability information, please visit our website. All LRV results are from Johnson Tiles' internal test reports and are to be used for guidance only. LRV: Light Reflectance Value.



Technical Data

Specification

Range	Size	Wall Suitability	Floor Suitability	Wet Barefoot	CSV	Material
Harbour	All Sizes Shown	Internal Only	-	-	VI	Glazed Ceramic [BIII]

Physical Properties

Test/Standard	Requirement	Test Result	Test/Standard	Requirement	Test Result
Length / Width EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	≤ ± 0.25%	Modulus of Rupture EN ISO 10545 - 4	Min. I5N / mm²	≥ 25N / mm²
Thickness EN ISO I 0545 - 2	± 10% ≤ ± 0.5mm	± 2.5%	Thermal Shock EN ISO 10545 - 9	Pass	Pass
Straightness of Side EN ISO 10545 - 2	± 0.3% ≤ ± 1.5mm	± 0.15%	Frost Resistance EN ISO 10545 - 12	-	Not Suitable
Rectangularity EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	± 0.4%	Chemical Resistance EN ISO 10545 - 13	Min. Class B	Class A - B
Surface Flatness EN ISO 10545 - 2	± 0.5% ≤ ± 2mm	± 0.3%	Stain Resistance EN ISO 10545 - 14	Min. Class 3	Class 3
Water Absorption EN ISO 10545 - 3	10% to 20%	15% to 17%	Fire Rating	-	Class A I Non Combustible
kg Weight / M²	16.67 kg 10mm thick				

Note: All products are classed as BIII - Glazed Ceramic. All products conform to BS EN 14411.

Range	Material	Recycled Content of the Tiles	Recycled Content of the Packaging	Recyclable Content of the Packaging	EPD
Harbour	Glazed Ceramic [BIII]	Up to 20%	Up to 100%	Up to 100%	Yes

Note: EPD: Environmental Product Declaration for the products shown in this overview can be on the Harbour pages on our website.

Important Information

During the manufacturing process of ceramic, vitrified and porcelain tiles, some variation in shade and pattern can occur. Before fixing any tiles; several boxes should be opened and their contents mixed to ensure that size, colour, shade and patterning are acceptable. The tiles shown are quality products and conform to the physical properties listed below.

- All sizes shown are metric modular.
- For specific suitability and fit-for-purpose details please contact our technical helpline.
- Johnson Tiles cannot accept responsibility for any tiles that have been fixed.
- \bullet Every effort has been made to ensure the accuracy of the information given.
- Johnson Tiles reserves the right to change specifications and availability without prior notice.
- Nothing in these statements does or will affect the statutory rights of the consumer.

® Johnson Tiles, Johnson, Absolute and Material Lab are registered trademarks and together with Kerastar and product names are the trademarks of H&R Johnson Tiles Limited and licensed to Norcros Group (Holdings) Limited trading as Johnson Tiles. © 2021 Johnson Tiles. All rights reserved.







For more information about Harbour or any of our other product ranges simply visit www.johnson-tiles.com | f > 0 p in D

Where To Find Us

Johnson Tiles

Harewood Street, Tunstall, Stoke on Trent, Staffordshire, ST6 5JZ

Tel: +44 (0)1782 575 575 Fax: +44 (0)1782 577 377 Email: info@johnson-tiles.com

Samples Enquiries

Tel: +44 (0) | 782 524 043 Fax: +44 (0) | 782 577 379

Email: samples@johnson-tiles.com

Technical Helpline

Email: techadvice@johnson-tiles.com

JOHNSON - TILES MADE IN THE UK SINCE 1901